



phone: (866) 564-8237
fax: (678) 247-2797
e-mail: hubermaterials@huber.com

www.hubermaterials.com

HYMOD® SB136 SG ALUMINUM HYDROXIDE (ATH)

DESCRIPTION

Huber Engineered Materials' Hymod SB136 SG is a coarse, mechanically ground, surface treated ATH product that provides hydrophobicity, flame retardancy and smoke suppression in a variety of applications, such as acrylic, EPDM, EVA, polyester and polyolefin compounds. The surface modification enables this product to have low moisture and to be easily and uniformly dispersed into polymers at high loading levels without causing processing rheology concerns.

TYPICAL CHEMICAL ANALYSIS

Al(OH) ₃ , %	99.6
SiO ₂ , %	0.007
Fe ₂ O ₃ , %	0.007
Na ₂ O (total), %	0.2
Na ₂ O (soluble), %	0.025
Loss on ignition (1000°C), %	34.6

TYPICAL PHYSICAL PROPERTIES

Screen Analysis	
% on 325 mesh	15
% through 325 mesh	85
% less than 10 microns	25
Median Particle Diameter, microns	18.5
BET Surface Area (m ² /g)*	1.5
Specific Gravity (g/cm ³)	2.42
Bulk Density - packed (g/cm ³)	1.2

© 2018 J.M. Huber Corporation. Hymod® is a registered trademark of J.M. Huber Corporation for surface treated aluminum hydroxide.

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Refer to Huber's Standard Conditions of Sale for the only express warranties applicable to the Huber products. Products incorporating Huber products are not warranted by Huber. In no event is Huber liable for consequential damages.

Revised 11/18