



3100 Cumberland Blvd.
Suite 600
Atlanta, GA 30339
phone: (866) 564-8237
fax: (678) 247-2797
e-mail: hubermaterials@huber.com

Kemgard 631

Typical Physical Properties

Composition	Proprietary Zinc / Aluminum Complex
Appearance	white powder
Specific Gravity	2.4
Surface Area (m ² /g)	10 - 12
Median Particle Size (um)	1.5 - 3.0
pH	10
Moisture (%)	<1
Residue on 325 Mesh Screen, % max.	0.1

Applications

Used for flame retardancy, smoke suppression, and antimony trioxide replacement in rigid and flexible PVC compounds.

Key Benefits:

- Highly effective Fire-Retardant additive for Flexible & Rigid PVC applications.
- Fire retardant with excellent LOI performance.

©2020 J.M. Huber Corporation. Kemgard[®] is a registered trademark of J.M. Huber Corporation.

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Refer to Huber's Standard Conditions of Sale for the only express warranties applicable to the Huber products. Products incorporating Huber products are not warranted by Huber. In no event is Huber liable for consequential damages.

Revised 6/21